



TECHNICAL DATA

AUTOMATIC DRIP CHECK

The Viking Corporation, 210 N Industrial Park Drive, Hastings MI 49058

Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-818-1680 Email: techsvcs@vikingcorp.com


1. DESCRIPTION

Viking Automatic Drip Checks are designed to drain water automatically, which may leak past a normally closed dry valve or deluge valve. They close, however, against an increase in flow pressure and will open automatically at a predetermined decrease in pressure. The devices are used with dry and deluge valves to drain any water that may seep by the valve clapper.

Model D-1 and D-4 Drip Check is used with a valve that does not have an automatic alarm line drain. It has a notched seat so that a slight amount of water will discharge through the drip check when the valve trips. When the control valve is closed, the alarm line will automatically drain through the drip check. This unit is normally used with the Viking Deluge Valves.

Model D-2 Drip Check is normally used with Viking Model C Dry Valves with iron trim. The drip check has a 3/8" pipe plug installed for use with the Model B-1 Accelerator. When the valve trips, no water will discharge through the drip check. When the control valve is closed and the system is drained, the drip check will open and drain off any excess water in the valve.

Model D-3 Drip Check is used with a Model D, E, or F Dry Valve that has an automatic drain for the alarm line. When the valve trips, no water will discharge through the drip check. When the control valve is closed and the system is drained, the drip check will open and drain off any excess water in the valve.



2. LISTINGS AND APPROVALS

Designed to Underwriter's Laboratory and Factory Mutual requirements.

3. TECHNICAL DATA

Specifications

Available since 1980.

Working water pressure: 250 PSI (17.2 bar)

Material Standards

Body: Brass casting UNS-C84400

Ball: Stainless Steel

Spring: Phosphor Bronze

Retaining Ring: Stainless Steel

Model D-4: Electroless Nickel Plated

Ordering Information

Automatic Drip Check, 3/4"

Model D-1 (Deluge & Flow Control Valves): Part Number 10730

Model D-2 (Dry Valve Replacement with Model B-1 Accelerator): Part Number 10731

Model D-3 (Dry Valve): Part Number 10732

Model D-4 (Deluge, Electroless Nickel Plated): Part Number 10733

Viking Technical Data may be found on The Viking Corporation's Web site at <http://www.vikinggroupinc.com>. The Web site may include a more recent edition of this Technical Data Page.

4. INSTALLATION

- A. Install in outlet provided in valve trim.
- B. Unit should be level.

5. INSPECTIONS, TESTS AND MAINTENANCE

During each inspection of valve, push plunger to make sure no water is trapped.

6. AVAILABILITY

The Viking Automatic Drip Check is available through a network of domestic and international distributors. See the Viking Corp. Web site for closest distributor or contact The Viking Corporation.

7. GUARANTEES

For details of warranty, refer to Viking's current list price schedule or contact Viking directly.